

MATERIAL SAFETY DATA SHEET

| CHEMICAL PRODUCT AND COMPANY IDENTIFICATION | | |
|---|-------------|--|
| PRODUCT | : | AMPRO HYDRAULIC OIL ISO 68 X |
| CODE | : | AMPRO205 |
| MANUFACTURER IDENTIFICATION | : | M/s United Grease And Lubricants P.O. Box 2685, Ajman, U.A.E. |
| BRAND OWNER | : | Al Maha Petroleum Products Marketing Company SAOG PO Box 57, Postal Code 116, Muscat, Sultanate of Oman |
| EMERGENCY PHONE NUMBER | : | 00971-6-7436521 |
| PRODUCT USE | : | HYDRAULIC OIL |
| COMPOSITION / INFORMATION ON INGREDIENTS | | |
| CHEMICAL NAME | CAS NO | WT |
| Zinc dialkyl dithiophosphate | 68649-42-3 | 0.6 |
| alkyl phenol | Proprietary | 0.2 |
| Mineral oil | 64741-88-4 | 99.2 |
| HAZARDS IDENTIFICATION | | |
| HAZARDS | : | UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT SHOULD NOT CAUSE ANY SIGNIFICANT HEALTH HAZARDS. HOW EVER A PROLONGED USE MAY CAUSE DERMATITIS. |
| FIRST AID MEASURES : | | |
| SKIN CONTACT | : | REMOVE CONTAMINATED CLOTHING, WASH SKIN IMMEDIATELY WITH WATER AND SOAP |
| EYE CONTACT | : | FLUSH WITH LARGE AMOUNT OF WATER, GET MEDICAL ATTENTION IF IRRITATION PERSISTS |
| INGESTION | : | DO NOT INDUCE VOMITING .GET MEDICAL ATTENTION |
| INHALATION | : | IN CASE OF EXPOSURE TO HIGH CONCENTRATION REMOVE PERSON TO FRESH AIR |
| FIRE FIGHTING MEASURES | | |
| FLASH POINT | : | 240 Deg C |
| EXTINGUISHING MEDIA | : | CO2, DRY CHEMICAL, OR FOAM.WATER SPRAY, DO NOT USE WATER JETS .THEY COULD CAUSE SPLATTERING. |
| ACCIDENTAL RELEASE MEASURES | | |
| ENVIRONMENTAL PROTECTION | : | SHUT OFF SOURCE OF SPILL .RECOVER FREE LIQUIDS BY USING APPROPRIATE TECHNIQUES.NOTIFY LOCAL AUTHORITIES |
| HANDLING AND STORAGE | : | HANDLING AND STORAGE TEMP. AMBIENT TO 85 Deg C |
| EXPOSURECONTROLS/PERSONAL PROTECTION | | |
| HAND/EYES/SKIN PROTECTION | : | WEAR GOGGLES, PROTECTIVE CLOTHING, GLOVES. |
| VENTILATION | : | NO SPECIAL VENTILATION REQUIRED |

| PHYSICAL AND CHEMICAL PROPERTIES | | |
|---|--------------------|---|
| APPEARANANCE | : | C&B |
| ODOUR | : | CHARACTERISTIC |
| COLOR | : | GOLDEN |
| DENSITY @ 15 Deg | : | 0.885Kg/L |
| FLASH POINT | : | 240 Deg C |
| SOLUBLITY | : | SOLUBLE IN HYDROCARBON SOLVENTS, INSOLUBLE IN WATER |
| STABILITY AND REACTIVITY | | |
| STABILITY | : | STABLE PRODUCT |
| HAZARDOUS REACTION | : | NONE |
| ECOLOGICAL INFORMATION GENERAL | : | NO SPECIFIC ENVIRONMENTAL DATA AVAILABLE |
| DISPOSAL CONSIDERATION | | |
| DISPOSAL OF PRODUCT | : | DO NOT DISPOSE OF THE PRODUCT EITHER NEW OR USED, BY DISCHARGING IN TO SEWERS, TUNNELS, LAKES OR WATER COURSES. |
| STORAGE CONDITIONS | : | HANDLING AND STORAGE TEMP. AMBIENT TO 40 Deg C |
| SHELF LIFE | : | 48 MONTHS AFTER THE DATE OF MANUFACTURING |
| TRANSPORT INFORMATION | | |
| NOT DANGEROUS FOR CONVEYANCUNDER UN, IMO,ADR/ RID AND IATA/CAO CODES | : | NOT REGULATED |
| REGULATORY INFORMATION | | |
| SYMBOL[S] | : | NONE |
| R PHRASE[S] | : | NONE |
| S PHRASE[S] | : | NONE |
| OTHER INFORMATIONS: | : | |
| R-PHRASES LISTED IN CHAPTER 2 | : | R41 RISK OF SERIOUS DAMAGE TO EYES R51/53 TOXIC TO ACQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT |
| PRODUCT INFORMATION | : | FOR SPECIFIC OR DETAILED TECHNICAL DATA FOR THIS PRODUCT, PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE. |
| HAZARD RATINGS | : | 4- Extreme 3- Serious 2- Moderate 1- Slight 0- Minimal |
| | : | See section 8 for more detailed Information on personal protection |
| The customer is responsible for determining the PPE code for this material | | |
| NOTICE FOR READER | | |
| To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. | | |
| The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC. | | |
| F/49 | Revision:00 | Issue Date:24/01/2020 |